

Addendum

1. a. JP
- b. 57076057 (abstract)
- c. Nippon Chem Ind Co. Ltd.
- d. 07-12-1982
- e. x

**COPY OF PAPERS
ORIGINALLY FILED**

Neomolekularbericht 1983

Nippon Chem. Ind. KK

V-02

JA 57 076 057 v. 31.10.80/12.5.82 (152 186), E 25

Polymere mit erhöhter Hitzestabilität

4340 [

enthalten ein Fettsäuresalz (Zinkstearat) und eine aktive Erdalkalimetallverbindung (Calciumhydroxid) mit einer Partikelgröße $\leq 10 \mu\text{m}$. Als Polymere werden u. a. PVC und halogeniertes Polyethylen genannt.

(Kr.) (H. 6104/83)

RESIN COMPOSITION

Patent Number: JP57076057
Publication date: 1982-05-12
Inventor(s): KASHIWASE HIROYUKI; others: 05
Applicant(s): NIPPON CHEM IND CO LTD:THE; others: 01
Requested Patent: ☐ JP57076057
Application Number: JP19800152186 19801031
Priority Number(s):
IPC Classification: C08L101/00; C08K3/18; C08K3/34; C08K5/09
EC Classification:
Equivalents:

Abstract

PURPOSE: To prepare the titled composition having suppressed blooming tendency and improved long-term thermal stability and light stability, by adding an additive based on higher fatty acids together with fine powder of specific alkaline earth metal compound to a resin.
CONSTITUTION: A resin composition containing a higher fatty acid or its derivative as a resin additive is compounded with 0.5-10mol % s, pref. 1-5mol, based on 1mol of the higher fatty acid or its derivative, of fine powder of an active alkaline earth metal compound having a diameter of essentially $\leq 10\mu\text{m}$ and selected from the oxide, hydroxide, amorphous silicate, amorphous aluminate or amorphous aluminosilicate of calcium or barium. The effect of the additive is remarkable when the resin is a halogen-containing resin.

Data supplied from the esp@cenet database - I2